



FLOW

The Flow is our newest innovation in LED profiles and is patented worldwide. Featuring our popular Optix S+ strip, pre-installed into a flexible, diffused profile.

Designed for ease of installation first and foremost, it can be cut anywhere with only a pair of scissors - no tools or saws required. The cut-free strip and flexible profile means it can be customised to fit any project size or shape, without compromising on light output and consistency.

Suitable for surface mounting or recessing, this is a truly versatile solution perfect for applications like acoustic panels where a beautiful ambient glow is required. Unlike rigid profiles the Flow is supplied on an easy to transport and space saving coiled reel of up to 5m.

BENEFITS
• Rollable: saving transportation cost and space
• Cuttable at any length, so there is no waste or dark spot.
• Designed specifically for acoustic panels
• Available in different widths and colours
• More flexibility and versatility
• Worldwide patent: P46355WO1

KEY FEATURES
• Dimmable
• Higher light density
• High lumens per watt
• High colour rendering index: >90
• Seamless transition between cool and warm colour temperatures

TECHNICAL SPECIFICATION	
Wattage	6W/m
Voltage	24V
Lumens (Light output)	580 lm/m
Lumens per Watt	100
Colour temperature	2700K - 6500K
Beam angle	180°
Colour rendering index	>90
Connector	2.5m at each end
No. LEDs per meter	512
Adhesive Tape	3M VHB (Very high bond)
Operating temperature	-30°C to +45°C



PRODUCT NAME	ORDER CODE	BARCODE
Flow 13mm + Optix S+ - 5M - Black - CCT	LLS022	5065027455382
Flow 13mm + Optix S+ - 5M - White - CCT	LLS023	5065027455399
Flow 19mm + Optix S+ - 5M - Black - CCT	LLS024	5065027455405

PRODUCT NAME	DIMENSIONS (mm)	WEIGHT (grams)	IP RATING
Flow 13mm + Optix S+ - 5M - Black - CCT	L 5000mm x W 13mm x D 5.5mm	200g	IP20
Flow 13mm + Optix S+ - 5M - White - CCT	L 5000mm x W 13mm x D 5.5mm	200g	IP20
Flow 19mm + Optix S+ - 5M - Black - CCT	L 5000mm x W 19mm x D 5.5mm	200g	IP20